

SIP

Line	Type	Number	Register	Invite with ID / Account	User ID / Account	Password	Confirm Password
FXS Representative Number			☐			*****	*****
FXO Representative Number			☐			*****	*****
1	FXS	2649689	☒	☒	2649689	*****	*****
2	FXS	777	☐	☐		*****	*****
3	FXS	2476187	☐	☐	2476187	*****	*****
4	FXS	804	☐	☐		*****	*****
5	FXO	004181202	☒	☒	004181202	*****	*****
6	FXO	806	☐	☐		*****	*****
7	FXO	807	☐	☐		*****	*****
8	FXO	808	☐	☐		*****	*****

Use DNS SRV	☒
DNS SRV Auto Prefix	☒
Proxy Fallback Interval [0 - 10800 s]	3600

☒	Enable Support of SIP Proxy Server / Soft Switch
☒	Enable SIP Proxy 1
Proxy Server IP / Domain	sipnet.ru
Proxy Server Port [1 - 65535]	5060
Proxy Server Realm	sipnet.ru
TTL (Registration interval) [10 - 7200 s]	600
SIP Domain	
Use Domain to Register	☐
☐	Enable SIP Proxy 2
Proxy Server IP / Domain	192.168.1.1
Proxy Server Port [1 - 65535]	5060
Proxy Server Realm	
TTL (Registration interval) [10 - 7200 s]	600
SIP Domain	
Use Domain to Register	☐
VoIP failure announcement	☐

Bind Proxy Interval for NAT [0 - 1800 s]	0
Initial Unregister	☐
Support Message Waiting Indication (MWI)	☐
MWI Subscribe Interval [0=disable, 60 - 86400 s]	7200

Outbound Proxy Support	☐
Outbound Proxy IP / Domain	
Outbound Proxy Port [1 - 65535]	5060

Session Expiration [0=disable, 10 - 1800 s]	0
Session Refresh Request	☒ UPDATE ☐ re-INVITE
Session Refresher	☒ UAS ☐ UAC

Enable P-Asserted	☐
Privacy Type	id

SIP Message Resend Timer Base [s]	
Max. Response Time for Invite [1 - 32]	8
Invite URL need 'user=phone'	☒
Reliability of Provisional Responses	☐
Compact Form	☒
SIP Caller ID Obtaining	
Put Caller ID In URI	☒
INVITE With Remote-Party-ID Header	☒
Support URI Percent-Encoding (RFC 3986)	☐
Compare SIP 'To' Header for Transit Out	☐
Enable SIP 'Allow' Header	☒
Call Hold Compatible With RFC 2543	☒
Enable SDP 'ptime' Attribute	☐
Use Redirect URI As 'To' Header (Receiving 3XX)	☐
Respond 'BUSY HERE' while no line available for hunting	☐

International Call Prefix Digit	10
Country Code	
Long Distance Call Prefix Digit	8
Area Code	499

E.164 Numbering	To Invite Proxy	☐
-----------------	-----------------	--------------------------

	Transform to Transit Out	☒
ENUM Header Exception	070	

Telephony Settings

Telephony Settings

Trunk Incoming Prompt Voice	☒ Default Greeting ☐ Custom Greeting ☐ Dial Tone
Custom Greeting Upload / Backup	Обзор... Upload Backup Clear Greeting
FXO Hunting VoIP call in option	Caller Indicate Dial-Out ▾
FXO Hunting Default Dial-Out	
FXO Line VoIP call in option	Caller Indicate Dial-Out ▾

Line	Enable	Type	Hot Line	Hot Line No.	Warm Line (Hot Line Delay) [0 - 60 s]	Dial-Out Prefix	FXO Line Default Dial-Out	FXS Group	Fax / Modem
1	☒	FXS	☐		0			☒	
2	☒	FXS	☐		0			☒	
3	☐	FXS	☐		0			☐	
4	☐	FXS	☐		0			☐	
5	☒	FXO	☒	2649689	0				
6	☐	FXO	☐		0				
7	☐	FXO	☐		0				
8	☐	FXO	☐		0				

Trunk Hunting Order	
Enable FXO / Trunk Extension Number	☒
Pick up Line by Dialing Extension Number	☒
Ring count before FXO pick up [0 - 999]	1
Transit In Busy Tone Limit [0 - 60 s]	3
Detect FXO Line Presence	☒

Ring (Early Media) Time Limit [10 - 600 s]	30
Enable End of Digit Tone	☐
VoIP Call Out Notification	☐
Enable Built-in Call Hold Music	☒
Force Calling Thru PSTN Code	
Trunk Early Media Option	
Early Media Treatment	☒
Loop Current Drop Trigger Time [0=disable, 3 - 30 s]	0
Loop Current Drop Duration [1 - 5 s]	2
Enable ROH	☐
FXS Ring Voltage [0=disable, 45 - 80]	0
FXS Onhook Voltage [0=disable, 24 - 57]	0
Max. External Call	999
VoIP Centrex Extension Digit Count [0=disable, 1 - 30]	0
VoIP Centrex Digit	

FXS Group Hunting / Ring Priority	
Hunting / Ring	
Sequential Ring Time [1 - 100 s]	6

1	Line 1	▽
2	Line 2	△ ▽
3		△ ▽

4		
---	----------------------	---

Telephony Settings

Trunk Incoming Prompt Voice	☒ Default Greeting ☐ Custom Greeting ☐ Dial Tone
Custom Greeting Upload / Backup	
FXO Hunting VoIP call in option	
FXO Hunting Default Dial-Out	
FXO Line VoIP call in option	

Line	Enable	Type	Hot Line	Hot Line No.	Warm Line (Hot Line Delay) [0 - 60 s]	Dial-Out Prefix	FXO Line Default Dial-Out	FXS Group	Fax / Modem
1	☒	FXS	☐		0			☒	
2	☒	FXS	☐		0			☒	
3	☐	FXS	☐		0			☐	
4	☐	FXS	☐		0			☐	
5	☒	FXO	☒	2649689	0				
6	☐	FXO	☐		0				
7	☐	FXO	☐		0				
8	☐	FXO	☐		0				

Trunk Hunting Order	
Enable FXO / Trunk Extension Number	☒

Pick up Line by Dialing Extension Number	☒
Ring count before FXO pick up [0 - 999]	1
Transit In Busy Tone Limit [0 - 60 s]	3
Detect FXO Line Presence	☒
Ring (Early Media) Time Limit [10 - 600 s]	30
Enable End of Digit Tone	☐
VoIP Call Out Notification	☐
Enable Built-in Call Hold Music	☒
Force Calling Thru PSTN Code	
Trunk Early Media Option	
Early Media Treatment	☒
Loop Current Drop Trigger Time [0=disable, 3 - 30 s]	0
Loop Current Drop Duration [1 - 5 s]	2
Enable ROH	☐
FXS Ring Voltage [0=disable, 45 - 80]	0
FXS Onhook Voltage [0=disable, 24 - 57]	0
Max. External Call	999
VoIP Centrex Extension Digit Count [0=disable, 1 - 30]	0
VoIP Centrex Digit	

FXS Group Hunting / Ring Priority	
Hunting / Ring	
Sequential Ring Time [1 - 100 s]	6

1	Line 1		
2	Line 2		
3			
4			